

Presskabelschuhe mit Langlöchern DIN

DIN

- **Werkstoff: 99,9% Elektrolyt-Kupfer, geglühtes Material**
- **Rohrabmessung nach DIN 46235**
- **Oberfläche: verzinkt, Ausführung mit 2 Langlöchern**
- **Pressmarkierung**



Cu

| Art. Nr. | LQ | M | KZ | d2 | d1 | d4 | A | I | c1 | c2 | kg/100 | VE |
|----------|------------|----|----|------|------|------|------|------|------|------|--------|----|
| 290550 | 70 | 12 | 16 | 13,0 | 11,5 | 16,5 | 28,0 | 55,0 | 13,0 | 13,0 | 10,800 | 25 |
| 290552 | 95 | 12 | 18 | 13,0 | 13,5 | 19,0 | 35,0 | 65,0 | 13,0 | 13,0 | 14,800 | 20 |
| 290554 | 120 | 12 | 20 | 13,0 | 15,5 | 21,0 | 35,0 | 70,0 | 16,0 | 17,0 | 18,600 | 25 |
| 290556 | 150 | 12 | 22 | 13,0 | 17,0 | 23,5 | 35,0 | 78,0 | 16,0 | 17,0 | 26,200 | 25 |
| 290558 | 185 | 12 | 25 | 13,0 | 19,0 | 25,5 | 40,0 | 82,0 | 16,0 | 17,0 | 26,800 | 10 |
| 290560 | 240 | 12 | 28 | 13,0 | 21,5 | 29,0 | 40,0 | 92,0 | 16,0 | 17,0 | 40,200 | 10 |

