

**ENVIRONMENTAL PRODUCT DECLARATION** 

# **Circuit Breaker size S3**

3RV2[0,1,3,7]4.-....

Type II according to ISO 14021 including life cycle impact assessment (LCIA)



# General information

This environmental product declaration (EPD) is based on the international standard ISO 14021 ("Environmental labels and declarations – Self declared environmental claims – Type II"). The data in this EPD has been evaluated on a full-scale life cycle assessment (LCA) study according to ISO 14040/44, taking into account the product category rules (PCR) for electronic and electrotechnical products and systems defined in EN 50693, as well as product specific rules (PSR) for low-voltage switchgear and control gear equipment in IEC TS 63058 ED1.0.


Siemens is dedicated to an environmentally conscious design of its products in line with IEC 62430 and has implemented an integrated management system according to ISO 9001, ISO 14001 and ISO 45001.

Products	All variants in the range of 3RV2[0,1,3,7]4			
Represented by	3RV2041-4JA10			
Product Description	Circuit breaker size S3 for motor protection, CLASS 10 A-release 4563 A N-release 819 A screw terminal Standard switching capacity			
Functional Unit	To make, carry and break currents at rated operation voltages Ue and for the utilization categories and N operations according to IEC 60947-4-1 by a manually operated mechanical switching device. To provide motor overload protection with a trip class according to IEC 60947-4-1. To provide short-circuit current protection. To provide isolation separation of a circuit in option			

## **Material composition**

The following chart outlines the overall material composition of the calculated reference product. Product weight of 2.25 kg adds up with packaging weight of 0.06 kg to a total weight of 2.31 kg. Packaging consists of Cardboard and Paper.

#### Product Weight 2.25 kg



### **Substance assessment**

At Siemens, we are committed to the development and production of environmentally sound and sustainably produced equipment. This includes avoiding hazardous substances in our products without compromising their benefits for our customers. Please visit the following website to learn more about how we comply with product-related environmental regulations like RoHS, REACH, WEEE and others: Product Related Environmental Protection

## Life cycle stages and reference scenarios



#### Manufacturing

This stage covers the extraction of natural resources, production of raw materials, manufacturing, packaging, and transport distances.



## Distribution and Operation

This stage covers the product's distribution, installation, use, and maintenance. Different operating conditions can lead to deviations from the reference scenario.



#### **End-of-Life**

This stage covers the disassembly, material recycling and thermal treatment of all recyclable materials as well as the disposal of all other materials.

#### **Scenarios**

#### **Energy model used:**

Europe (renewable mix), Europe (standard mix)

## Transportation model used:

100km default distance, GLO: truck-trailer, Euro IV

#### **Energy model used:**

Europe (standard mix)

#### **Distribution scenario:**

Truck-trailer, up to 28t gross weight 3500.0 km

#### Use scenario:

34 W full load, 50% loading rate, 50% service uptime: reference lifetime 20 years

#### **Energy model used:**

EME/

#### **End-of-life methodology**

Avoided burden (net-scrap calculation)

## **Key environmental performance indicators**

The following impact categories characterize the product's environmental footprint. They have been calculated with LCIA methodology EF3.1; LCA tool: Green Digital Twin (GDT), Database: One Siemens LCA Database (based on MLC CUP 2023.2, formerly GaBi).

To ensure the high quality and completeness of the LCA results, Primary Data have been used whenever possible. Datasets for resources, such as electrical energy or natural gas, are chosen from the region where the device is produced and assembled. If primary data are not available, datasets reflecting state-of-the-art manufacturing technology are considered.


Impact Category	Unit	Total	Manufacturing	Distribution	Operation	End of Life
Acidification	Mole of H+ eq	6.82E-01	1.24E-01	1.45E-03	5.75E-01	-1.93E-02
Climate change – total	kg CO2 eq	2.83E+02	1.85E+01	1.24E+00	2.65E+02	-1.50E+00
Climate change – fossil	kg CO2 eq	2.81E+02	1.84E+01	1.23E+00	2.63E+02	-1.49E+00
Climate change – biogenic	kg CO2 eq	2.46E+00	8.62E-02	5.26E-03	2.37E+00	-5.64E-03
Ecotoxicity, freshwater – total	CTUe	2.60E+03	5.15E+02	1.16E+01	2.08E+03	-8.37E+00
Eutrophication, freshwater	kg P eq	8.93E-04	1.23E-04	4.47E-06	7.70E-04	-4.34E-06
Eutrophication, marine	kg N eq	1.43E-01	1.43E-02	4.74E-04	1.29E-01	-1.46E-03
Eutrophication, terrestrial	Mole of N eq	1.50E+00	1.53E-01	5.67E-03	1.36E+00	-1.50E-02
Human toxicity, cancer – total	CTUh	8.32E-08	2.71E-08	2.40E-10	5.99E-08	-3.96E-09
Human toxicity, non-cancer – total	CTUh	2.90E-06	8.59E-07	1.30E-08	2.19E-06	-1.68E-07
lonising radiation, human health	kBq U235 eq	1.30E+02	1.94E+00	4.62E-03	1.28E+02	8.25E-03
Land Use	dimensionless (pt)	1.77E+03	4.54E+01	6.95E+00	1.72E+03	-5.44E-01
Ozone depletion	kg CFC-11 eq	4.16E-09	3.22E-10	1.23E-13	3.85E-09	-1.64E-11
Particulate matter	Disease incidences	6.18E-06	1.78E-06	9.75E-09	4.77E-06	-3.84E-07
Photochemical ozone formation, human health	kg NMVOC eq	3.90E-01	4.51E-02	1.25E-03	3.49E-01	-5.79E-03
Resource use, fossils	MJ	4.98E+03	2.36E+02	1.64E+01	4.76E+03	-2.42E+01
Resource use, mineral and metals	kg Sb eq	3.42E-03	4.03E-03	1.27E-07	7.19E-05	-6.78E-04
Water use	m³ water eq deprived water	7.97E+01	2.16E+01	1.40E-02	5.91E+01	-1.04E+00

## **Climate Change**


This chart shows the overall impact of the product on climate change – total. The operations phase is the lifecycle phase with the biggest overall impact. Different operating conditions can lead to deviations from the reference scenario. The distribution stage of the reference product is not shown in the chart due to its relatively small contribution to climate change and its impact is included in the operation bar.







#### kgCO2eq





## **End-of-Life results**

The end-of-life stage was modelled by shredding of the device, followed by sorting and material separation process.

It leads to:

- an overall product recyclability of up to 62% mainly due to high metal content
- an energy recoverability of up to 29% from plastic materials
- a minimum disposal rate of 8%

The exact final values depend on the used recycling process and add up to 100%.

**Note:** The device should not be disposed of as unsorted municipal waste. Special treatment for specific components may be mandated by law or recommended for environmental reasons. Observe all local and applicable laws.

# Legal Disclaimer

## This Environmental Product Declaration (EPD) is for information purposes only. It is based upon the standards mentioned above.

This EPD does not warrant or guarantee the composition of a product or that the product will retain a particular composition for a particular period. Therefore, all warranties, representations, conditions, and all other terms of any kind whatsoever implied by statute or common law are – to the fullest extent permitted by applicable law – excluded.

Siemens therefore does not assume any liability for any error or for any consequence which may arise from the use of this information to the maximum extent under the law.

Please be aware that the data of this EPD cannot be compared with data calculated based upon product category rules (PCRs) other than the standards mentioned above. The values given are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

#### Published by Siemens AG

#### Smart Infrastructure

**Electrical Products** 

Werner-von-Siemens-Str. 48 92224 Amberg Germany

Subject to changes and errors.

The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

All product designations may be trademarks or product names of Siemens AG or other companies whose use by third parties for their own purposes could violate the rights of the owners.

© 2023 by Siemens AG, Berlin and Munich