



Type	57682		
Designation.....	Eco Charger Multi Pro		
System to charge	NiMH (Nickel Metal Hydride)	Charge Indicator.....	green LED
Cell sizes.....	AAA or AA	charging	blinking slow
Cell configuration.....	1-8 cells (single slot charging) AA or AAA	defective/wrong cell	blinking fast
		charging complete	solid green
Input.....	5V = 1...3A / 5...15W	Safety Features	Wrong cell (alkaline) detection
Plug/cable length.....	USB C Plug / 1m USB C to USB C cable included		Wrong polarity detection (mechanical)
			Short circuit detection
			Low input voltage detection
Charging currents and cut off Timer.....		Housing Material.....	ABS
3A Source	AA: 1-2 2000mA ±10% / 1.7h AA: 3-4 1400mA ±10% / 2.5h AA: 5-8 700mA ±10% / 5h AAA: 1-4 1000mA ±10% / 1.5h AAA: 5-8 700mA ±10% / 2h	Housing colour.....	Light Grey/Green
5V/2A Source	AA: 1-2 1000mA ±10% / 3.5h AA: 3-4 700mA ±10% / 5h AA: 5-8 350mA ±10% / 10h AAA: 1-4 700mA ±10% / 2h AAA: 5-8 350mA ±10% / 4h		
5V/1A Source	AA: 1-2 500mA ±10% / 7h AA: 3-4 350mA ±10% / 10h AA: 5-8 200mA ±10% / 17.5h AAA: 1-4 350mA ±10% / 4h AAA: 5-8 200mA ±10% / 7h		
Maintenance charge current.....	AAA 50mA for 1h AA 100mA for 1h	Dimensions	Charger:
Charge Termination	-dV and temperature cut off	Length	125.5 ± 1 mm
		Width	137.5 ± 1 mm
		Height	29 ± 1mm
		Weight	168 ± 3g

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries